

# Finger Safe Power Distribution Blocks

## UL Approved for 100kA

- Mersen Finger-Safe PDB's meet k100A Short Circuit Current Rating (SCCR) per UL 1059

(Reference: UL File E73571)

- Preferred by electrical panel shops to meet latest requirements of NEC and UL508a
  - SCCR Rated
  - Touch Safe
  - Wide Product Offering
  - Availability



Mersen Part No.	Amps	SCCR	WIRE RANGE		REQUIRED OVERCURRENT PROTECTION					
			Line	Load	Class J (AJT, A4J, HSJ)	Class T (A3T/A6T)	RK1 (A2D/A6D) (A2K/A6K) HSRK	RK5 (TR/TRS)	Class G (AG)	Class CC (ATDR, ATQR, ATMR)
FSPDB1A	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB1C	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB2A	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB2C	175	100KA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB3A	310	100KA	350-#6 & 2/0-#14	2/0-#14	400A	400A	400A	200A	60A	30A
FSPDB3C	310	100KA	350-#6 & 2/0-#14	2/0-#14	400A	400A	400A	200A	60A	30A

USA T 978 462 6662 F 978 462 0181 info.nby@mersen.com

CANADA T 416 252 9371 F 416 252 6572 sales.tor@mersen.com

[ep.mersen.com](http://ep.mersen.com)

**MERSEN**  
Ferraz Shawmut is Mersen